

Easy-to-use various functions

Lay-in Type Thread Tension Slots

Simply raising the presser foot and passing thread straight through the slot threads the tension disc. Even thick thread is easy to thread.



Slit-Type Molded Looper Threading Paths

Since troublesome threading of the thread take-up lever is no longer required, the machine head can be threaded with ease only by passing the thread along the groove.



Adjustable Stitch Length/Differential Feed

▼ Stitch length adjustment dial




▼ Differential feed adjustment dial




Stretchy fabrics

Materials that stretch easily such as knit fabrics can be finished beautifully using shirring stitch.



Materials that stretch easily such as knit fabrics can be finished beautifully using shirring stitch.



Materials that are likely to cause stitch gathering can be finished beautifully using stretching stitch.


Lower Looper Threader

Threading the lower looper can easily be done by operating a lever.




Automatic Rolled Hemming

Simply pulling a lever toward you easily switches the machine to rolled hemming.



Threading of the Chain Stitch Looper

The looper can easily be threaded since it can be lowered at the press of a button.



Other Features

- 3-step adjustment of the presser foot pressure
- Exterior thread cutter
- Safety mechanism that prevents the machine from running even when you depress the foot controller with the looper cover left open

Optional Attachments

Cover Stitch Hem Guide

Part No.40122229




Blind Stitch Presser Foot

Part No. A9810-634-0A0A
(For use with right needle only)




Universal Blind Stitch Presser Foot

Part No. A9521-634-0A0A
(For use with left or right needle)



Elasticator Presser Foot

Part No. A9815-655-0A0A




Piping Presser Foot

Part No. A9865-655-0A0A



Cording Presser Foot

Part No. A9820-655-0A0A



Beading Presser Foot

Part No. A9870-634-0A0A



Curved Beading Presser Foot

Part No. A9511-634-0A0A



Gathering Presser Foot

Part No. A9860-655-0A0C

Attachments are also available in 3, 6 and 8 piece sets

JUKI
JUKI CORPORATION



2-11-1, TSURUMAKI, TAMA-SHI, TOKYO
206-8551, JAPAN
<https://www.juki.co.jp>

JUKI CORPORATION holds the rights to change technical specifications without prior notice. 2107(WL)

MO-735N

JUKI

Top-of-the-line overlock machine with a wide variety of stitches that ensures professional-grade finished product quality



Easily change from overlock to cover stitch!

Overlock settings

Cover stitch settings



MO-735N

2-Needle, 2/3/4/5-Thread Overlock with Cover Stitch and Chain Stitch

The machine supports all basic stitch patterns such as overlock, cover stitch, chain stitch and 5-thread safety stitch. With this machine, you get finished products of professional-grade quality.



Cover Stitch

Perfect for various applications, such as simple hems, sleeve cuffs and necklines. Because the stitching stretches, it is ideal for stretch fabrics.

4-Thread Cover Stitch 3-Thread Cover Stitch (wide) 3-Thread Cover Stitch (narrow)



Chain Stitch

Because the lower thread forms a chain on the wrong side of the fabric, the stitch is strong when it is stretched, making it ideal for stitching the waist and side seams of pants. It also does well as decorative stitching for necklines.




MO-735N

2-Needle, 2/3/4/5-Thread Overlock with Cover Stitch and Chain Stitch
Dimensions: 300 (W) x 260 (D) x 290 (H) mm
Weight: 9 kg


Overlock Stitches

5-Thread Safety Stitch




This is the stitch type that combines 3-thread overlock and chain stitch. This stitch type produces durable seams and is frequently used for joining sides of shirts, for example.

4-Thread Overlock




Uses 2 needles and 4-threads to securely sew together knitted fabrics.

3-Thread Overlock



This basic stitch prevents fabric from fraying.

3-Thread Rolled Hem



The fabric edge is rolled, then covered with thread.

3-Thread Narrow Overlock




The fabric edge is rolled, then sewn with very narrow overlocking.

Frill 3-Thread Rolled Hem with Diff. Feed




Uses 3-thread rolled hemming and the differential feed on stretch fabrics to create richly designed pieces.

3-Thread Flatlock



This stitch type is used to accentuate clothing, interior goods and small articles. Since lace thread and wool yarn can be used for sewing the decorative part (as upper looper thread), this seams serve as unique design element of the work.

2-Thread Overcast



Simply sew fabric edges with 2 threads to prevent fraying.

▲ 2-thread converter is included.

MO-735N Standard Specifications


Number of Threads	2/3/4/5 threads
Sewing Speed	Maximum 1,500spm
Seam Width	5-7 mm (4-Thread overlock / 3/2-Thread overlock / 3-Thread super stretch)
	3-5 mm (3/2-Thread overlock)
	8-10 mm (5-Thread safety stitch)
Needle	SCHMETZ 130/705H or JLx2
Stitch Length	1-4 mm (Standard: 2.5mm)
Differential Feed	0.7-2.0 Ratio
Presser Foot Lift	6 mm
Weight	9 kg
Dimensions	300 (W) x 260 (D) x 290 (H) mm
Foot Control Model	YC-483N (220-240V)

Packed with many useful functions!

Cover Stitch Variation

Stitch width can be selected.

For the 4-thread cover stitch, stitch width is 5 mm. For the 3-thread cover stitch, stitch width is 5 mm (wide) or 2.5 mm (narrow).



Upper knife releasing system and the auxiliary bed for cover stitch/chain stitch.


Auxiliary bed provided with a scale that serves as a material edge guide and is helpful for sewing.

For cover stitch or chain stitch, the auxiliary bed that is helpful for sewing should be installed. In this case, the upper knife can be released to provide a wider work space.



Release of the Presser Foot Pressure (Standard Presser Foot)

When sewing cover stitch, uneven material feed can be effectively reduced by releasing the standard presser foot pressure. The presser foot pressure is minimized by tilting the presser foot pressure release lever to the rear.



Presser Foot Lifter

The presser foot is higher at its tip in order to allow the fabric to easily be inserted at the start of sewing. In addition, raising the presser foot lifter to the first position raises the presser foot 6 mm.

Further raising the presser foot lifter raises the front of the foot is automatically lifted. This allows you to easily insert thick layers of fabric, for example, when attaching ribbing, under the presser foot.



▲ LED Light



▲ Accessory Storage